

AIR PAC



Model #AP4

Specification:

Four individually controlled all-purpose deck ovens in a compact stack design. Each oven utilizes a unique energy delivery system of controlled hot air flow for fast, consistent operation. Offers minimum preheat time, consistent selected temperatures, high quality production and menu versatility. Available in 208 or 240 volt - 3 Phase only.



Standard Features:

- Stainless steel front, sides, top, and legs
- Four Heavy-duty pull-down front doors
- Removable bottom jet plate
- Adjustable steel wire oven rack (2 positions) one per-deck
- Electronic controls with precision timers
- Single speed fan with ¼ HP motor (0.5 kW)
- 4.7 kW element package per deck
- Leveling and front-locking casters
- 1 year limited parts & labor warranty on ovens

Optional Features:

- Extra Stainless Steel wire rack (s)
- Adjustable perforated stainless steel pizza deck (two positions)

Note: Ovens supplied with casters must be installed with an approved restraining device.

Garland Commercial Industries, Inc.
 185 East South Street
 Freeland, Pennsylvania 18224
 Phone: (570) 636-1000
 Fax: (570) 636-3903

Garland Commercial Ranges Ltd
 1177 Kamato Road, Mississauga, Ontario
 L4W 1X4 CANADA
 Phone: 905-624-0260
 Fax: 905-624-5669

Enodis UK LTD
 Swallowfield Way, Hayes, Middlesex
 UB3 1DQ ENGLAND
 Telephone: 081-561-0433
 Fax: 081-848-0041



Item #: _____
 Model: AP4
 Product Name: Electric Four Compartment Deck Oven

Oven Interior Dimensions*			Exterior Dimensions			Shipping Wt. Lbs./Kg	
Width	Height	Depth	Width	Height	Depth	Crated	Uncrated
19-1/4" (489mm)	4-3/4" (121mm)	17-3/4" (451mm)	36-1/2" (927mm)	64-3/4" to 66" (1145mm) to (1676mm)	34-1/4" (870mm)	800/363	650/295

*With rack in place Two fixed rack positions: 1-1/8" (28mm) and 1-5/8" (41mm)

Installation Notes				
Combustible Wall Clearance			Entry Clearance	
Left	Right	Rear	Crated	Uncrated
0" (0mm)	6" (152mm)	6" (152mm)	44" (1118mm)	35" (889mm)

Electrical Requirements	kW Loading 240V/208V	Three Phase (only) Nominal Amperes Per Line For Each Circuit					
NOTE: Two Circuits Required	20.8 Total 10.4 (per Circuit)	240V			208V		
		X	Y	Z	X	Y	Z
		28	22	28	32	26	32

AIR PAC

